

PLEXIGLAS® GS Blocks

Product

From a thickness of 30mm onward, cast PLEXIGLAS® sheets are classed as blocks.

Properties

In addition to the well-known and proven properties of PLEXIGLAS®, such as

- excellent light transmission and brilliance
- extremely high weather resistance
- ease of fabrication
- high surface hardness
- low weight – half the weight of glass
- 11 times the impact strength of glass
- 100% recyclability,

PLEXIGLAS® blocks offer the following special features:

- absolute transparency for an undistorted view
- resistance to several tonnes of water pressure
- resistance to solvents and chemicals

Applications

These properties make PLEXIGLAS® GS block material particularly suitable for

- aquarium glazing such as cylinders, tunnels, flat and curved glazing supported on four and three sides. Larger sizes can be produced using butt joints;
- swimming pool glazing
- architecture featuring light and water
- glazing of pressure equipment such as submersibles, and hyperbaric chambers for medical use
- artwork and decoration
- model-building and prototypes
- furniture construction
- illuminated signs

Machining

PLEXIGLAS® block material can be machined just like standard PLEXIGLAS®. The following Guidelines for Workshop Practice are available for PLEXIGLAS®:

- Machining PLEXIGLAS® (Ref. No. 311-1)
- Forming PLEXIGLAS® (Ref. No. 311-2)
- Joining PLEXIGLAS® (Ref. No. 311-3)
- Surface Treatment of PLEXIGLAS® (Ref. No. 311-4)
- Fabricating Tips for PLEXIGLAS® Solid Sheet (Ref. No. 311-5)

Physical forms

PLEXIGLAS® block material is available in the following sizes and thicknesses:

Standard size: 3000 x 2000 [mm]

Special sizes: 5000 x 2000 [mm],
6000 x 2200 [mm], 6000 x 3000 [mm] and
7800 x 3000 [mm]

Standard thicknesses: 30 – 80 [mm]

Special thicknesses: up to 180 [mm]

The material is available in transparent, translucent or opaque colors. Satin surfaces can be provided on one or both sides. The material can also be supplied with special product properties such as higher chemical resistance, or UV transmission.

You will find more details in the PLEXIGLAS® Sales Handbook Typical properties

For typical values, please consult the Technical Information sheet on PLEXIGLAS® GS/XT (211-1).

Certificates are available for special applications

- EU Pressure Equipment Directive
- Classification and Construction Regulations III Marine Technology (Underwater Technology, Diving Units) of Germanischer Lloyd
- SAFETY STANDARD FOR PRESSURE VESSELS FOR HUMAN OCCUPANCY ASME PVHO-1-2007

® = registered trademark PLEXIGLAS is a registered trademark of Evonik Röhm GmbH, Darmstadt, Germany. Certified to DIN EN ISO 9001 (Quality) and DIN EN ISO 14001 (Environment)

Evonik is a worldwide manufacturer of PMMA products sold under the PLEXIGLAS® trademark on the European, Asian, African and Australian continents and under the ACRYLITE® trademark in the Americas.

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Performance Materials GmbH

Acrylic Polymers

Kirschenallee, 64293 Darmstadt, Germany
info@plexiglas.net www.plexiglas.net www.evonik.com

Ref-No. 222-18 July 2015